



## CRC MOTOR FLUSH

Ref. : 10335

### 1. GENERAL DESCRIPTION

---

Fast motor flush.

A blend of highly active polar and non-polar solvents, paraffinic oil, dispersant and anti-wear additives.

CRC Motor Flush cleans the engine's interior of sludge, gum, rust and varnish prior to oil change.

### 2. FEATURES

---

- Dissolves deposits from pistons and rings and frees sticky valves and lifters.
- Holds the deposits in suspension until they are drained with the oil.
- Contains anti-wear, anti-corrosion and anti-oxidation additives protecting the engine whilst flushing it.
- Helps to restore compression.
- Improves performance, fuel economy and engine life.
- Non-acid, non-alkaline and non-corrosive.
- Harmless to all metal parts.
- Can be used in diesel as well as in gasoline engines.
- Compatible with all commonly used types of oil.

### 3. APPLICATIONS

---

- Motor bikes
- Cars
- Trucks
- Busses
- Boats
- Farm and garden equipment
- Stationary combustion engines

### 4. DIRECTIONS

---

- Shake before use.
- Pour content of can into crankcase, whilst engine is warm.
- Run engine for about 10 minutes at increased idle, 1500 rpm., then switch off and drain out old oil.
- Replace oil filter, as required.
- Refill with clean engine oil.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





## CRC MOTOR FLUSH

Ref. : 10335

### 5. TYPICAL PRODUCT DATA (without propellant)

---

Appearance	: amber liquid
Specific gravity @ 20° C	: 0.83
Pour point	: <-20°C
Flash point (open cup)	: 65°C
Solvent blend properties	
- Distillation range	: 170-250°C

### 6. PACKAGING

---

Bottle: 12 x 375 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10335 03 0198 02  
Date : 15 June 2007



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

